

Specifikacije

Model	Platinum 100 3G	Platinum 200 3G	Platinum 300 3G	Platinum C250 3G
Format	2-stazni	3-stazni	3-stazni	3-stazni
Frekventni opseg (-6dB) na otvorenom	37 Hz – >60 kHz	32 Hz – >60 kHz	25 Hz – >60 kHz	48 Hz – >60 kHz
Frekventni odgovor (-6dB) u prostoru	28 Hz – >60 kHz	23 Hz – >60 kHz	17 Hz – >60 kHz	30 Hz – >60 kHz
Osetljivost (2.83v @ 1m)	85 dB	88 dB	88 dB	88 dB
Nominalna impedanca	4 Ohma	4 Ohma	4 Ohma	4 Ohma
Minimalna impedanca	4 Ohma @ 180 Hz	4.0 Ohma @ 2.5 kHz	4.0 Ohma @ 3.75 kHz	4.0 Ohma @ 150 Hz
Continuirana snaga (RMS na 4 Ohma, Pink Noise i 6dB Crest Factor)	150 W	300 W	400 W	300 W
Preporučena snaga pojačala (RMS na 4 Ohm, muzički signal)	75 - 300 W	150-600 W	200-800 W	150-600 W
Podešavanje basa	HiVe II sustav otvora	HiVe II sustav otvora	Dvostruki HiVe II sustav otvora	Zatvorena
Rezna frekvencija	LF/HF: 2.85 kHz	LF/MF: 825 Hz/MF/HF: 3 kHz	LF/MF: 650 Hz/MF/HF: 3 kHz	LF/MF: 850 Hz/MF/HF: 3.5 kHz
Frekvencija podešavanja otvora	44 Hz	38 Hz	32 Hz	N/A
Ugrađene jedinice	1 x 152 mm RDT III niskotonac, 1 x MPD III visokotonac	2 x 152 RDT III niskotonac, 1 x 100 RDT III srednjetonac, 1 x MPD III visokotonac	2 x 200 mm RDT III niskotonac, 1 x 100 mm RDT III srednjetonac, 1 x MPD III visokotonac	2 x 152 RDT III niskotonac, 1 x 63 mm RDT III srednjetonac, 1 x MPD III visokotonac
Vanjske dimenzija uključivo mrežice i terminali (VŠD)	398 x 225 x 325 mm	1023.2 (1031.4)* x 368 x 454 mm	1112.7 (1120.9)* x 430 x 525 mm	
Vanjske dimenzije uključivo prošireno podnožje i šiljci (VŠD)	N/A	1039.7 (1047.9)* x 368 x 454 mm	1129.2 (1137.4)* x 430 x 525 mm	N/A
Masa (svaki)	15.2 kg	35.8 kg	53.6 kg	25.4 kg
Završna obrada	Glasovir lak crna i ebanovina, mat bijela			

