7.2-CHANNEL NETWORK A/V RECEIVER



Prepare for the 8K Cinema Revolution

High-spec HDMI® unlocks exciting features for gamers and film lovers in your family, including 8K video passthrough, HDR10+, and low-latency gameplay. Enjoy DTS:X® and Dolby Atmos® 3D soundtracks with refined Integra power and convenient voice-controllable multi-room audio.

AUDIO & VIDEO HIGHLIGHTS

- 5.2.2-ch Dolby Atmos® and DTS:X® playback
- DTS Virtual:X™ and Dolby Atmos Height Virtualization
- Dolby Surround® and DTS® Neural:X upmixing
- HDMI®¹1 supports 8K/60p (4:4:4/12-bit², 4:2:2/12-bit², 4:2:0/10-bit), 8K/30p (4:4:4/12-bit², 4:4:4/10-bit, 4:2:2/12-bit), 4K/120p (4:4:4/12-bit², 4:4:4/10-bit, 4:2:2/12-bit) video passthrough, HDR10+, Dolby Vision™, HDR10, HLG, BT.2020, VRR (Variable Refresh Rate), DSC (Display Stream Compression), ALLM (Auto Low Latency Mode), QFT (Quick Frame Transport), QMS (Quick Media Switching), eARC (enhanced Audio Return Channel), DeepColor™, x.v.Color™, LipSync, and HDCP 2.3
- HDMI Main Out with eARC for encoded HQ audio, Sub/Zone 2 Out with OSD*
- Bidirectional Bluetooth® wireless technology Version 4.2 + LE (A2DP v1.2, AVRCP v1.3; RX: SBC/AAC, TX: SBC/Qualcomm® aptX"/apt X HD)
- Separate Zone 2 speaker outputs enable 5.2.2-ch + Zone 2 speaker connection, 5.2.2-ch playback switching to 5.2-ch + Zone 2 playback⁴
- Dedicated Zone 2 DAC supports synced/independent D/A audio distribution (including HDMI/SPDIF/NET's) via Zone 2 speaker outputs and Zone 2 pre-out's
- Share any MAIN audio source to a wireless headphone dock via Zone B line-out⁻⁶
- Phono equalizer (MM) and SACD (Super Audio CD) playback via HDMI (2.8 MHz 2-ch/multichannel)
- AccuEQ Room Calibration with subwoofer EQ and AccuReflex[™]
- Original DSP-based Vocal Enhancer clarifies in-program vocals/dialog

AMPLIFICATION TECHNOLOGY

- 160 W per channel (6 $\Omega,$ 1 kHz, 10% THD, 1-ch driven)
- 135 W per channel (6 $\Omega,$ 1 kHz, 1% THD, 1-ch driven, IEC)
- Low-impedance amp system with 4-ohm speaker-driving capability
- Massive custom transformer and hand-selected audio parts
- Non-phase-shift amp-circuit topology for clear and cohesive sound
- Optimum Gain Volume Circuitry
- Precision DAC supports 192 kHz/24-bit multichannel D/A conversion
- VLSC™ (Vector Linear Shaping Circuitry) filtering technology (Front L/R)
- PLL (Phase-Locked Loop) jitter-cleaning circuitry for SPDIF digital audio
- Front L/R speaker bi-amping capability in 5.2-ch configuration
- Tone controls (bass/treble) for Front L/R channels

NETWORK & MULTI-ZONE AUDIO FEATURE

- Isolated quad-core SoC board supports high-speed 802.11ac (2x2 MIMO'7) Wi-Fi®
- \bullet Supports Amazon Music HD $^{\circ}$, Spotify $^{\circ}$, TIDAL, TuneIn, and Deezer $^{\circ}$
- \bullet Works with Sonos supporting multiple Sonos Connect/Port control and Volume Passthrough mode 10
- \bullet Works with Alexa supporting multi-room music $^{^{*}11}$
- \bullet Works with Ok Google $^{\mbox{\tiny 12}}$ and Chromecast built-in $^{\mbox{\tiny TM}}$
- AirPlay 2 multi-room audio with Siri voice control
- DTS Play-Fi® supports Critical Listening mode via Integra Music Control App*13
- \bullet Compatible with the Integra Remote app for iPad, iPhone, and Android $^{\text{\tiny{IM-13}}}$
- Roon Tested certified for the Roon Core
- Hi-Res Audio via network (DSD 11.2 MHz/5.6 MHz/2.8 MHz⁻¹⁴, FLAC, WAV [RIFF], ALAC, and AIFF to 192 kHz/24-bit⁻¹⁵)

AUDIO-VIDEO CONNECTIONS

- 6 HDMI inputs, Main Out (eARC), Sub/Zone 2 Out
- 2 digital audio inputs (rear, 1 optical, 1 gold-plated coaxial, assignable)
- 4 gold-plated analog RCA audio inputs (rear, assignable)
- Gold-plated phono input and built-in equalizer (MM) for turntable connection
- USB input (5 V/1 A) for audio playback (rear)
- Gold-plated 3.5 mm AccuEQ setup mic input (front)
- Gold-plated 6.35 mm headphone jack
- 9 gold-plated speaker posts with transparent knobs (including Zone 2)
- Dedicated gold-plated Zone 2 speaker outputs*4
- Gold-plated Front L/R pre-out, Zone 2 pre-out, and Zone B line-out (analog RCA*6)
- 2 subwoofer pre-outs
- Ethernet LAN terminal

CUSTOM INTEGRATION FEATURES

- 10BASE-T/100BASE-TX Ethernet supports setup and IP control via web browser
- \bullet Works with Crestron®, Control4®, Savant, URC, ELAN, and RTI automation
- RS-232 input for external control and automation
- 2 IR inputs and 1 output
- 3 programmable 12 V trigger-outs with adjustable delay (A: 100 mA, B: 25 mA, C: 25 mA)
- Dealer-settings memory storage and recall function
- AC inlet for detachable IEC power cable
- Optional rack-mount kit (IRK-155-3D)

ADDITIONAL FEATURES

- Aluminum front panel and volume knob
- One-touch volume memory preset assignment to individual A/V inputs via front panel
- Dolby® TrueHD and DTS-HD Master Audio® decoding
- OSD function displays A/V input signal data, output signal/settings data, and network information.
- Advanced Music Optimizer™ improves compressed audio playback quality
- High-definition GUI over HDMI
- 4K to 8K, 1080p to 8K/4K video upscaling via HDMI
- Crossover Adjustment (40/45/50/55/60/70/80/90/100/110/120/130/150/180/200 Hz)
- A/V Sync Control (Up to 500 ms in 1 ms steps at 48 kHz*16)
- Sleep timer, HDMI passthrough, and network standby
- 40 FM/AM/internet radio presets with station-naming (10 characters)
- 3-Mode display dimmer (Normal/Dim/Dimmer)

I Features defined in HDMI 2.1 specification, HDR10+, and passthrough capabilities described are supported on HDMI inputs 1-3, Main Out, and Sub/Zone 2 Out in Sub Mode output. *2 DSC signals only. *3 HDMI Zone 2 Mode output supports signals via HDMI inputs 1-3. *4 Playback via Height (5.2.2-ch layout) Surround Back (7.2-ch layout) speaker outputs is unavailable when playing in 5.2-ch + Zone 2 Speaker output mode, Output via Zone 2 speaker output and Zone 2 pre-out, tenabled. *5 Zone 2 HDMI audio is available on inputs 1-3. SPDIF and HDMI support PCM signals only, *6 Zone 2 pre-out, Zone 8 line-out, and front LJR pre-out are exclusive modes shared on the same analog RCA output. *7 Some countries or regions have regulations that affect wireless signal strength and the use of Wi-Fi channels. *8 Amazon Music HD is supported via DTS Play-Fi* '9 Service availability varies with region, and a paid subscription may be required. *10 Requires Sonos Connect or Port (sold separately). Connection of 1-2 Sonos devices is supported with volume control enabled via the Sonos app. Sonos app available free for compatible iPhone and iPad at the App Store. Available free for compatible Android devices at the Google Play Store. *11 Voice control requires an Amazon Alexa enabled device. Alexa multi-room music may require a firmware update. *12 Voice control requires a Google Assistant enabled device. *13 Available free for compatible iPhone, iPad, and Android devices. *14 Converted to PCM. Playback not guaranteed via wireless LAN. *15 Supported sampling rates may vary depending on network environment. LAC is supported to a maximum 96 kHz. *16 Max. 400 ms (1 ms steps) at 96 kHz, and max. 200 ms (1 ms steps) at 192 kHz.

7.2-CHANNEL NETWORK A/V RECEIVER





COMPATIBLE WITH **■■Dolby** Vision

■■Dolby Atmos



🚣 deezer

*** TIDAL











































SPECIFICATIONS

AMPLIFIER SECTION

Power Output Front L/R:

Dynamic Power:

Input Sensitivity and Impedance:

THD+N (Total Harmonic Distortion + Noise):

Rated RCA Output Level and Impedance:

Phono Overload:

Frequency Response: Tone Control:

Signal-to-Noise Ratio:

160 W/Ch at 6 Ω, 1 kHz, 10%, 1 Channel Driven, 135 W/Ch at 6 Ω, 1 kHz, 1%,

1 Channel Driven, IEC

160 W (3 Ω, Front) 125 W (4 Ω, Front) 85 W (8 Ω, Front)

200 mV rms/47 kΩ (Line/Unbalance) 3.5 mV rms/47 kΩ (Phono MM)

0.08% (20 Hz-20 kHz, Half Power) 1 V rms/470 Ω

(Pre-out/Subwoofer Pre-out)

200 mV rms/470 kΩ (Zone B Line-out) 70 mV (MM, 1 kHz, 0.5%)

10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode)

±10 dB, 20 Hz (Bass) ±10 dB, 20 kHz (Treble) 106 dB (IHF-A, Line) 80 dB (IHF-A, Phono)

Speaker Impedance: 4 Ω–16 Ω

TUNER SECTION

FM 87.5 MHz–108 MHz AM 522/530 kHz–1,611/1,710 kHz Tuning Frequency Range:

FM/AM Preset Memory: 40 Stations

GENERAL

AC 220-240 V~. 50/60 Hz Power Supply:

Power Consumption: 450 W Standby Power Consumption: 0.15 W


435 x 174 x 376.5 mm Dimensions (W x H x D):


9.8 kg Weight:

CARTON

Dimensions (W x H x D): 560 x 305 x 467 mm

Weight: 12.5 kg





W	Н	D	а	b
435 mm	174 mm	376.5 mm	435 mm	155 mm
С	е	f	g	i
24.5 mm	330.5 mm	21.5 mm	1.5 mm	229.5 mm
j	k	1	m	n
42.5 mm	60.8 mm	433 mm	71.5 mm	167.5 mm