

# PRO-650T-RK

## 6.5" ROCK SATELLITE



### HIGH PERFORMANCE OUTDOOR AUDIO

With a 6.5" IMG woofer and a Tractrix horn-loaded 1" Aluminum Dome Tweeter, the Pro-650T-RK rock satellite speaker uses the same high performance acoustic design philosophies of our legendary indoor products, bringing the world's most dynamic, powerful, detailed sound to your outdoor living space.

### ALL NEW TRACTRIX HORN

For decades, our proprietary Tractrix horn design has brought high efficiency, low distortion, and superb dynamics to every Klipsch product. By designing an all-new custom Tractrix horn for the PRO-650T-RK, we've been able to optimize those acoustic properties while providing ultra-wide 105° horizontal dispersion - for a powerful, balanced sound in every listening position.

### 8 OHM / 70V / 100V COMPATIBILITY

From small residential systems to massive commercial installs, the Klipsch Pro Series rock speakers are designed to make any installation job quick and easy. For distributed line application, the Pro-650T-RK features a 50 watt, 70V/100V multi-tap transformer with 8 ohm bypass, allowing for perfect balance at any listening location, all selectable from a easily accessible, tool-free rotary switch on the bottom of the speaker.

### ALL-WEATHER DURABILITY

A UV-resistant, mechanically reinforced fiberglass cabinet provides the utmost in all-weather cabability, while weatherproof acoustic materials and stainless steel hardware ensure reliability in even the harshest of environments. With an IP45 rating, the Klipsch Pro-650T-RK is lab tested and certified to offer the best in outdoor audio year in and year out.

### SPECIFICATIONS

<b>FREQUENCY RANGE</b>	100Hz - 24kHz +/- 3dB 92Hz - 30kHz +/- 6dB 77Hz - 35kHz +/- 10dB
<b>HIGH FREQUENCY DRIVER</b>	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
<b>LOW FREQUENCY DRIVER</b>	6.5" (16.51cm) IMG Woofer
<b>SENSITIVITY</b>	90 dB
<b>COVERAGE ANGLE</b>	105°
<b>POWER HANDLING</b>	100W Peak
<b>70V / 100V TAP SETTINGS</b>	70V: 6.25W, 12.5W, 25W, 50W 100V: 12.5W, 25W, 50W 8 Ohm Bypass
<b>ENCLOSURE MATERIAL</b>	UV Treated Fiberglass Cabinet
<b>FINISHES</b>	Granite (1063230), Sandstone (1063229)
<b>PRODUCT DIMENSIONS</b>	10.91" x 9.65" x 13.43" (277mm x 245mm x 341mm)
<b>PRODUCT WEIGHT</b>	11 lbs (4.98 kg)
<b>BUILT FROM</b>	2017