

# Monitor Audio Climate 50

|   |  |  |
|---|--|--|
| <b>Frequency Response</b><br>75 Hz — 30 kHz   | <b>Sensitivity (1W@1M)</b><br>87 dB                                    | <b>Nominal Impedance</b><br>8 ohms                     |
| <b>Maximum SPL</b><br>106.8 dBa   | <b>Power Handling (RMS)</b><br>80 W                                    | <b>Recommended Amplifier Requirements</b><br>10 — 80 W |
| <b>Drivers</b><br>1x 140 mm (5 1/2") C-CAM bass/ mid-range driver<br>1 x 25 mm (1") C-CAM Gold Dome tweeter | <b>External Dimensions (H x W x D)</b><br>285 mm x 172.5 mm x 158.5 mm | <b>Overall Depth (Including Bracket)</b><br>210 mm     |
| <b>Total Bracket Pivot Angle</b><br>87.5 degrees (from central position)                                    | <b>Fixed Angled Block (Portrait)</b><br>15 degrees                     | <b>Connection</b><br>Gold plated 'push' type terminals |
| <b>Environmental Protection Rating</b><br>IP55  | <b>Colour / Finish</b><br>White/Black                                  | <b>Weight (packaged)</b><br>3.66 kg                    |
| <b>Sold As</b><br>Pair  |  |  |