



	E3 LCR v2	E5 LCR v2	E7 LCR v2
<b>DESIGN</b>	3-driver, dual passive radiators, 2-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System, Machined Aluminum Baffle	4-driver, dual passive radiators, 3-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System, Machined Aluminum Baffle	4-driver, dual passive radiators, 3-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System, Machined Aluminum Baffle
<b>CROSSOVER</b>	3rd-order electro-acoustic at 2.3 kHz	3rd-order electro-acoustic at 3 kHz 2nd-order electro-acoustic @ 450 Hz	3rd-order electro-acoustic at 3 kHz 2nd-order electro-acoustic @ 480 Hz
<b>HIGH FREQUENCY DRIVER</b>	1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology	Coaxial 1" (2.5cm) Aluminum Magnesium Ceramic AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) and Perforated Phase-Aligning (PPA™) Tweeter Lens, Patented Dual-Sync™ Continuous Flux Motor	Coaxial 1" (2.5cm) Aluminum Magnesium Ceramic AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) and Perforated Phase-Aligning (PPA™) Tweeter Lens, Patented Dual-Sync™ Continuous Flux Motor
<b>MIDRANGE</b>	--	Coaxial 6" (15.2cm) AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 2" high-temp multi-layered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor	Coaxial 6" (15.2cm) AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 2" high-temp multi-layered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor
<b>BASS/MIDRANGE (E3 LCR ONLY) BASS (E5/E7 LCR ONLY)</b>	Two 5.5" (13.9cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, 1.5" high-temp voicecoil, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 6.5" (16.5cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, 1.5" high-temp voicecoil, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 8" (20.3cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, 1.5" high-temp voicecoil, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
<b>PASSIVE RADIATORS</b>	Two 5.5" (13.9cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 6.5" (16.5cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 8" (20.3cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
<b>LOW FREQ. EXTENSION*</b>	57 Hz	56 Hz	55 Hz
<b>FREQUENCY RESPONSE</b> (0-15 degree window)	±3 dB from 93 Hz - 22 kHz	±3 dB from 82 Hz - 22 kHz	±3 dB from 80 Hz - 22 kHz
<b>FREQUENCY RESPONSE</b> (30-45 degree window)	±3 dB from 93 Hz - 19 kHz	±3 dB from 82 Hz - 19 kHz	±3 dB from 80 Hz - 19 kHz
<b>SENSITIVITY - ROOM</b>	92 dB	94 dB	95 dB
<b>SENSITIVITY - ANECHOIC</b>	89 dB	91 dB	92 dB
<b>SUITABLE AMP POWER RANGE</b>	15-200 W	15-220 W	15-220 W
<b>MAXIMUM INPUT POWER</b>	130 W	150 W	150 W
<b>IMPEDANCE</b>	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms
<b>DIMENSIONS WITH GRILLE</b> (H x W x D)	32" x 7-5/8" x 4-1/8" (81.4cm x 19.5cm x 10.5cm)	43" x 9-1/2" x 4-1/8" (109.2cm x 19.5cm x 10.5cm)	43" x 9-1/2" x 4-1/8" (109.2cm x 19.5cm x 10.5cm)
<b>CUT-OUT DIMENSIONS</b>	31" x 6-5/8" (78.8cm x 16.0cm)	42" x 8-1/2" (106.6cm x 21.5cm)	42" x 8-1/2" (106.6cm x 21.5cm)
<b>MINIMUM MOUNTING DEPTH</b> (Distance behind 1/2" drywall, or similar material)	3-7/8" (9.8cm)	3-7/8" (9.8cm)	3-7/8" (9.8cm)
<b>WEIGHT</b>	23.0 lbs (10.4 kg)	34.0 lbs (15.4 kg)	33.0 lbs (14.9 kg)
<b>FINISH</b>	White, paintable grille, black speaker	White, paintable grille, black speaker	White, paintable grille, black speaker
<b>ACCESSORIES</b>	PB-3	PB-5/7	PB-5/7

## TECHNICAL SPECIFICATIONS

All specifications are subject to change without notice.