



	P1 LCR v2	P3 LCR v2	P5 LCR v2
<b>DESIGN</b>	3-driver, 2-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System	3-driver, dual passive radiators, 2-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System	4-driver, dual passive radiators, 3-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System
<b>CROSSOVER</b>	2nd-order electro-acoustic at 2.2 kHz	2nd-order electro-acoustic at 2.2 kHz	3rd-order electro-acoustic at 2.8 kHz, 2nd-order electro-acoustic @ 500 Hz
<b>HIGH FREQUENCY DRIVER</b>	1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology	1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology	1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology
<b>MIDRANGE</b>	--	--	6.5" (16.5cm) Coaxial AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 1" high-temp multi-layered voice coil with Apical™ former
<b>BASS/MIDRANGE (P1/P3 LCR ONLY) BASS (P5 LCR ONLY)</b>	Two 5.5" (13.9cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 5.5" (13.9cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 6.5" (16.5cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
<b>PASSIVE RADIATORS</b>	--	Two 5.5" (13.9cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets	Two 6.5" (16.5cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
<b>LOW FREQ. EXTENSION*</b>	74 Hz	66 Hz	65 Hz
<b>FREQUENCY RESPONSE</b> (0-15 degree window)	±3 dB from 94 Hz - 22 kHz	±3 dB from 86 Hz - 22 kHz	±3 dB from 84 Hz - 22 kHz
<b>FREQUENCY RESPONSE</b> (30-45 degree window)	±3 dB from 94 Hz - 19 kHz	±3 dB from 86 Hz - 19 kHz	±3 dB from 84 Hz - 19 kHz
<b>SENSITIVITY - ROOM</b>	92 dB	93 dB	94 dB
<b>SENSITIVITY - ANECHOIC</b>	89 dB	90 dB	91 dB
<b>SUITABLE AMP POWER RANGE</b>	15-120 W	15-120 W	15-200 W
<b>MAXIMUM INPUT POWER</b>	90 W	90 W	130 W
<b>IMPEDANCE</b>	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms
<b>DIMENSIONS WITH GRILLE</b> (H x W x D)	20-5/8" x 7-5/8" x 4-1/8" (52.4cm x 19.4cm x 10.5cm)	32" x 7-5/8" x 4-1/8" (81.3cm x 19.4cm x 10.5cm)	43" x 9-1/2" x 4-1/8" (109.2cm x 24.1cm x 10.5cm)
<b>CUT-OUT DIMENSIONS</b>	19-5/8" x 6-5/8" (49.8cm x 16.8cm)	31" x 6-5/8" (78.7cm x 16.8cm)	42" x 8-1/2" (106.6cm x 21.6cm)
<b>MINIMUM MOUNTING DEPTH</b> (Distance behind 1/2" drywall, or similar material)	3-7/8" (9.8cm)	3-7/8" (9.8cm)	3-7/8" (9.8cm)
<b>WEIGHT</b>	15.0 lbs (6.8 kg)	19.0 lbs (8.6 kg)	29.0 lbs (13.2 kg)
<b>FINISH</b>	White, paintable grille, black speaker	White, paintable grille, black speaker	White, paintable grille, black speaker
<b>ACCESSORIES</b>	PB-1	PB-3	PB-5/7

## TECHNICAL SPECIFICATIONS

All specifications are subject to change without notice.