

INGROUND SUBWOOFERS

Design

Bass Driver

Low Frequency Extension

Frequency Response (0-15 degree window)

Sensitivity — Outdoor

Sensitivity — Anechoic

Suitable Amplifier Power Range

Maximum Input Power

Impedance

Dimensions (h x d)

Weight

Finish

GO10SW 10" Inground Subwoofer

Inground subwoofer with single high excursion driver (band-pass), 5/8" (14.3 cm) thick high-density polyethylene (HDPE) enclosure

10" (25.4 cm) high compliance, mica-filled polypropylene with stitched Nitrile-Butadiene Rubber (NBR) surround, 2" high-power oversized voice coil, 4-layer on fiberglass bobbin

Oversized 2.0" high-power, 4-layer on fiberglass bobbin

33 dB from 33 Hz - 135 kHz

88 dB

82 dB

15 - 1000 watts

400w

Compatible with 8 ohms

24" (height) x 18" (depth)
(60.9 cm x 45.7 cm)"

48 lbs (21.8 kg)

Textured Copper

GO12SW 12" Inground Subwoofer

Inground subwoofer with single high excursion driver (band-pass), 5/8" (14.3 cm) thick high-density polyethylene (HDPE) enclosure

12" (31 cm) high compliance, mica-filled polypropylene with stitched Nitrile-Butadiene Rubber (NBR) surround, 2.5" high-power oversized voice coil, 4-layer on fiberglass bobbin

Oversized 2.5" high-power, 4-layer on fiberglass bobbin

33 dB from 28 - 120 Hz

91 dB

85 dB

15 - 1000 W

500w

Compatible with 8 ohms

33" (height) x 35" (depth)
(83.8 cm x 88.9 cm)"

62 lbs (28.1 kg)

Textured Copper