Stylus® Series	Stylus [®] 170	Stylus [®] 270	Stylus [®] 370	Stylus® 370-SM	Stylus [®] 470	Stylus® 470-SM
Design	2-driver, 2-way acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure	2-driver, 2-way acoustic suspension, weather, water, UV-resistant PolyGlass [™] enclosure	2-driver, 2-way acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure	Single speaker system with stereo L/R inputs, 3-driver, 2 x 2-way acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure	2-driver, 2-way acoustic suspension, weather, water, UV-resistant PolyGlass [™] enclosure	Single speaker system with stereo L/R inputs, 3-driver, 2 x 2-way acoustic suspension, weather, water, UV-resistant PolyGlass [™] enclosure
Crossover(s)	3rd-order electro-acoustic at 2.3 kHz	3rd-order electro-acoustic at 2.3 kHz	3rd-order electro-acoustic at 2.3 kHz	Two 3rd-order electro-acoustic at 2.3 kHz	3rd-order electro-acoustic at 2.3 kHz	Two 3rd-order electro-acoustic at 2.3 kHz
High-Frequency Driver(s)	25-mm (1 in) PTD™ dome	25-mm (1 in) PTD™ dome	25-mm (1 in) PTD™ dome	Two 25-mm (1 in) PTD™ domes	25-mm (1 in) PTD™ dome	Two 25-mm (1 in) PTD™ domes
Bass/Midrange Driver	115-mm (4-1/2 in) ICP [™] cone	140-mm (5-1/2 in) ICP™ cone, die-cast chassis	165-mm (6-1/2 in) ICP™ cone, die-cast chassis	Dual voice-coil, 165-mm (6-1/2 in) ICP™ cone, die-cast chassis	190-mm (7-1/2 in) ICP™ cone, die-cast chassis	Dual voice-coil, 190-mm (7-1/2 in) ICP™ cone die-cast chassis
Low-Frequency Extension*	65 Hz (DIN)	60 Hz (DIN)	55 Hz (DIN)	55 Hz (DIN)	50 Hz (DIN)	50 Hz (DIN)
Frequency Response: <i>On-Axis</i> 30° Off-Axis	± 2 dB from 90 Hz $-$ 20 kHz ± 2 dB from 90 Hz $-$ 18 kHz	±2 dB from 85 Hz – 20 kHz ±2 dB from 85 Hz – 18 kHz	±2 dB from 80 Hz – 20 kHz ±2 dB from 80 Hz – 18 kHz	±2 dB from 80 Hz – 20 kHz ±2 dB from 80 Hz – 15 kHz	±2 dB from 75 Hz – 20 kHz ±2 dB from 75 Hz – 18 kHz	±2 dB from 75 Hz — 20 kHz ±2 dB from 75 Hz — 15 kHz
Sensitivity — Outdoor	88 dB	90 dB	91 dB	91 dB	93 dB	93 dB
Suitable Amplifier Power Range	15 — 80 watts	15 - 90 watts	15 — 100 watts	15 – 100 watts Mono; 15 – 50 watts/channel Stereo Input	15 — 110 watts	15 — 110 watts Mono; 15 — 55 watts/channel Stereo Input
Maximum Input Power†	50 watts	60 watts	70 watts	70 watts Mono; 35 watts/channel Stereo Input	80 watts	80 watts Mono; 40 watts/channel Stereo Input
Impedance	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 8 ohms	Compatible with 4 ohms Mono; 8 ohms/channel Stereo Input	Compatible with 8 ohms	Compatible with 4 ohms Mono; 8 ohms/channel Stereo Input
Height, Width, Depth	19.4 cm x 14.2 cm x 14.0 cm 7-3/4 in x 5-10/16 in x 5-1/2 in	24.0 cm x 17.9 cm x 17.6 cm 9-1/2 in x 7 in x 7 in	27.3 cm x 19.3 cm x 18.8 cm 10-3/4 in x 7-10/16 in x 7-6/16 in	27.3 cm x 19.3 cm x 18.8 cm 10-3/4 in x 7-10/16 in x 7-6/16 in	32.0 cm x 22.6 cm x 22.1 cm 12-10/16 in x 8-14/16 in x 8-3/4 in	32.0 cm x 22.6 cm x 22.1 cm 12-10/16 in x 8-14/16 in x 8-3/4 in
Weight (unpacked)	1.6 kg / 3.4 lb each	3.1 kg / 6.8 lb each	4.0 kg / 8.8 lb each	3.8 kg / 8.3 lb each	4.8 kg / 10.6 lb each	4.8 kg / 10.6 lb each
Finishes	Black, White	Black, White	Black, White	Black, White	Black, White	Black, White