

# Technical Specifications

## SATELLITE SPEAKERS

### Design

### GO4 4" Satellite Speaker

2-driver, 2-way outdoor satellite, acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure

### GO6 6" Satellite Speaker

2-driver, 2-way outdoor satellite, acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure

### Crossover

2nd-order electro-acoustic at 2.5 kHz

2nd-order electro-acoustic at 2.5 kHz

### High Frequency Driver

3/4" (1.9 cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, Perforated Phase-Aligning (PPA™) Tweeter Lens, die-cast low diffraction baffle/heat sink

3/4" (1.9 cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, Perforated Phase-Aligning (PPA™) Tweeter Lens, die-cast low diffraction baffle/heat sink

### Bass/Midrange Driver

4" (10 cm) mineral-filled polypropylene cone, Nitrile-Butadiene Rubber (NBR) surround

6" (16 cm) mineral-filled polypropylene cone, Nitrile-Butadiene Rubber (NBR) surround

### Low Frequency Extension

100 Hz

100 Hz

### Frequency Response (0-15 degree window)

± 3 dB from 120 Hz - 20 kHz

± 3 dB from 90 Hz - 20 kHz

### Sensitivity — Outdoor

87 dB

92 dB

### Sensitivity — Anechoic

83 dB

88 dB

### Suitable Amplifier Power Range

15 - 120 W

15 - 120 W

### Maximum Input Power

60 W

80 W

### Impedance

Compatible with 8 ohms

Compatible with 8 ohms

### Dimensions (diameter x depth)

5-1/4" (diameter) x 8" (depth)  
13.4cm x 20.3cm

7" (diameter) x 10" (depth)  
17.8cm x 25.4cm

### Weight

4.3 lbs (2.6 kg)

5.7 lbs (2.9 kg)

### Finish

Satin Bronze

Satin Bronze